

DATA SHEET	250 SC	300 SC
Engine	2 stroke Sherco proprietary design	
Cilindrada	249.70cc	294.00cc
Bore x Stroke	72.80 x 60 mm	79 x 60 mm
Cylinder	Nikasil	
Carburator	KEIHIN Ø 28	
Lubrification	2% oil pre-mix	
Fuel	Unleaded gasoline 98 Octane	
Cooling	Liquid system	
Start	Geared system with folding lever	
Exhaust	Stainless steel exhaust pipe with an integrated aluminium muffler	
Transmission	5 speed sequential gearbox with security selector system. Primary gear drive chain secondary drive	
Clutch	Hydraulic, diaphragm system	
Ignition	Hidria Digital	
Chassis	Tubular Chrome-Moly	
Fuel tank	Polyamide - 2,4 L (0.63 US Gal) capacity	
Brakes	Hydraulically activated, floating Ø 185 mm (7.28 in) front - Ø 145 mm (5.70 in) rear	
Front suspension	Hydraulic steel fork Ø 40 mm – 170 mm travel	
Rear suspension	Hydraulic monoshock – 165 mm travel	
Front wheel	MORAD 21" black aluminium rim	
Rear wheel	MORAD 18" black aluminium rim	
Wheelbase	1322 mm	
Ground clearance	310 mm	
Seat height	685 mm	

